

INNERBOND 1900L LIGHTWEIGHT SPACKLING PASTE

Innerbond 1900L Lightweight Spackling Paste is a water based product that is scientifically formulated not to shrink, crack or break even when used to make large repairs. It is excellent for patching wood, plaster, sheetrock, stucco and masonry.

PHYSICAL PROPERTIES

Weight per gallon	4.25 lbs	Consistency	Soft Smooth Paste
Shelf life	1 Year	Tack free time	1 Hour at 73°F
Temperature Range	-5°F to 180°F	Color	White

SURFACE PREPARATION

Surface must be clean, dry and free from dirt, dust, grease, mildew, wax and loose paint. Spackling must be applied in temperatures above 50°F. New or unpainted porous surfaces should be primed prior to patching.

APPLICATION

1. Apply with putty knife and press firmly into void.
2. If thinning is required, use up to 1 teaspoon per ½ pint of paste.
3. When used on exterior surfaces, product must be painted when dry with an oil or latex paint.

LIMITATIONS

Must be applied in temperatures above 50°F.

PACKAGING

Innerbond 1900L Lightweight Spackling Paste is available in pint and quart containers.

CAUTION

Innerbond 1900L Lightweight Spackling Paste may irritate eyes, avoid direct contact. In case of eye contact, flush eyes with water for at least 10 minutes and call a physician. Avoid breathing dust when sanding.

Keep from freezing and close container after use.

NOTE

The information and data contained herein are believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of use. Since Inland, Inc. cannot know all of the uses to which its products may be put or the conditions of use, it makes no warranties concerning the fitness or suitability of its products for a particular use or purpose.

Thorough testing of our product on any proposed use should be conducted prior to each application. It is the responsibility of the consumer to evaluate the performance of our product in each given application. Likewise, if the manner in which our products are used requires governmental approval or clearance, it is the user's responsibility to obtain it.

Inland, Inc. warrants only that each product will meet its specifications. There is no warranty of merchantability or fitness for use, nor any other expressed or implied warranties. The user's exclusive remedy and Inland, Inc.'s sole liability is limited to replacement of any product shown to be otherwise than as warranted. Inland, Inc. will not be liable for incidental or consequential damages of any kind.

Suggestions of uses should not be taken as inducements to infringe any patents.