

MATERIAL SAFETY DATA SHEET



INNERBOND C-600 Concrete & Mortar Filler

SECTION I – PRODUCT AND COMPANY IDENTIFICATION

DATE: September 12, 2007

MANUFACTURER'S NAME: INLAND, INC.
 ADDRESS: P. O. BOX 644 (42702)
 209 PETERSON DRIVE
 ELIZABETHTOWN, KY 42701
 TELEPHONE NUMBER: 270-737-6757

EMERGENCY CONTACT: CHEMTREC 800-424-9300

NFPA = NATIONAL FIRE PROTECTION ASSOCIATION
 HEALTH (NFPA): 1 FLAMMABILITY (NFPA): 1 REACTIVITY (NFPA): 0
 CAS NO: MIXTURE
 GENERIC DESCRIPTION: SEALANT

SECTION II - HAZARDOUS COMPONENTS

CAS Number	Substance	Wt. %	TLV	PEL	Units
1317-65-3	Calcium Carbonate (as nuisance particulate, total)*	56.0	10	15	mg/m ³
	mixture				
	Acrylic Terpolymer	<25	NE	NE	NA
85-68-7	Butyl Benzyl Phthalates	<7.0	NE	NE	NA
64742-88-7	Mineral Spirits (petrol. dist.)	1.2	100	100	ppm
7664-41-7	Aqua Ammonia	<0.25	NA	NA	ppm

*Inhalation of particulate unlikely due to product's physical state.
 The above components are hazardous as defined in 29 CFR 1910.1200.

SECTION III – HAZARDS IDENTIFICATION

Eyes: Contact can cause irritation.
Skin: Prolonged or repeated contact may cause mild skin irritation
Inhalation: High vapor concentrations may produce headache, dizziness and nausea.
Ingestion: May be harmful if swallowed.

SECTION IV - FIRST AID MEASURES

Eyes: Flush with large amounts of water while holding the eyelids open. Get medical attention if irritation persists.
Skin: Wipe off and wash with soap and water. Get medical attention if irritation persists.
Inhalation: Remove to fresh air. Treat with artificial respiration if needed.
Ingestion: Contact local poison control center or physician immediately!

SECTION V - FIRE FIGHTING MEASURES

Flash Point: >200°F
Ignition Temperature: Unknown
Flammability Limits in Air: Unknown
Extinguishing Media: Carbon dioxide, dry chemical, or foam
Special Fire Fighting Procedures: Use water spray or fog to cool fire-exposed containers.
Unusual Fire and Explosion Hazards: None

MATERIAL SAFETY DATA SHEET

INNERBOND C-600 Concrete & Mortar Filler

SECTION VI - ACCIDENTAL RELEASE MEASURES

Containment/Clean up: Wipe up spilled material. Wash area with detergents. Dispose of in accordance with local, state and federal regulations.

SECTION VII - HANDLING AND STORAGE

Avoid contact with skin and eyes. Keep away from children. Keep container tightly closed. Keep container in a cool, dry place. Avoid freezing & excessive heat. Avoid accidental ingestion.

SECTION VIII - EXPOSURE CONTROLS AND PERSONAL PROTECTION

Respiratory Protection: Not normally required. If TLV is exceeded, or for symptoms of overexposure, wear NIOSH-approved respirator for organic vapors.

Hand Protection: Not normally required; in situations of extended skin contact, neoprene or other chemical resistant gloves are recommended.

Eye Protection: Safety glasses with side shields

Ventilation: Provide adequate general dilution ventilation.

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

Physical Form: Paste
Odor: Mild acrylic odor
Boiling Point (at 760 MM HG): Not established
Volatiles by volume (%): <20
Specific Gravity (at 77°F/25°C): 1.6
Vapor Pressure (at 77°F/25°C): Not established
Vapor Density (Air = 1 at 77°F/25°C): >1
pH 8.2 – 8.8
Evaporation Rate (Butyl Acetate = 1): >1.0
Solubility in Water: Appreciable

The above information is not intended for use in preparing product specifications.

SECTION X – STABILITY AND REACTIVITY

Chemical Stability: Stable
Hazardous Decomposition Products: Carbon monoxide, Carbon dioxide (CO₂)
Incompatibility (Materials to Avoid): None known

SECTION XI – TOXICOLOGICAL INFORMATION

No known applicable information.

SECTION XII – ECOLOGICAL INFORMATION

No known applicable information.

SECTION XIII – DISPOSAL CONSIDERATION

According to 40 CFR 261, this material is not classified as a hazardous waste. State and local laws may impose additional regulatory requirements regarding disposal.

MATERIAL SAFETY DATA SHEET

INNERBOND C-600 Concrete & Mortar Filler

SECTION XIV – TRANSPORT INFORMATION

US DOT & Canada TDG Surface: Not regulated
Transport by sea IMDG-Code: Not regulated
Air transport ICAO-TI/IATA-DGR: Not regulated

SECTION XV – REGULATORY INFORMATION

FEDERAL REGULATIONS:

This product does not contain materials that are federally regulated.

U.S. STATE REGULATIONS:

California Proposition 65 Carcinogens:

This material contains chemicals known to the state of California to cause cancer, birth defects or other reproductive harm.

Butyl Benzyl Phthalate

SECTION XVI – OTHER INFORMATION

This data is offered in good faith as typical values and not as a product specification. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate.